Phase Equilibria Diagrams

Phase Diagrams for Ceramists

Volume XI Oxides

BEST AVAILABLE COPY

General Editor Robert S. Roth

Associate Editors
Howard F. McMurdie, ACerS
Helen M. Ondik, ACerS

Managing Editor
Mary A. Clevinger, NIST

Typesetting Editor Kimberly M. Hill, ACerS

を · 一切 · 日本のは · 一切 · 日本の ·

十二十二 報告報告前衛官等以及各項

Graphics Editor Thomas Green, ACerS

Editorial Assistant Christina L. Cedeno, ACerS Graphics Associates Evans Hayward, ACerS Nils Swanson, ACerS

Text and Typesetting Systems Carla G. Messina, ACerS

Graphics Systems
Peter K. Schenck, NIST

Compiled in the Ceramics Division.

National Institute of Standards and Technology
Gaithersburg, Maryland 20899

The American Ceramic Society
735 Ceramic Place, Westerville, Ohio 43081



これのは神神の神神のないのはなるないのはないないないできる

からなる のはなる あんしょう



NSRDS

The National Standard Reference Data System comprises a set of data centers and other data evaluation projects coordinated by the Standard Reference Data Program of the National Institute of Standards and Technology (NIST). The aim of this program is to provide reliable reference data on physical, chemical, and materials properties to the scientific and technical communities of the United States. Evaluated data produced under the program are made available in a variety of publications and computer-readable databases through joint projects of NIST and other interested groups, in this case the American Ceramic Society.

The phase diagrams published in this volume were collected and reviewed by the Phase Diagrams for Corumists Data Center, located in the Materiuls Science and Engineering Laboratory of the National Institute of Standards and Technology. Significant support from the American Ceramic Society was crucial in providing this important reference information to the ceramics community.

John R. Rumble, Jr.
Acting Chief, Standard Reference Data Program
National Institute of Standards and Technology

ISBN 0-944904-90-4

Copyright © 1995, The American Ceramic Society All rights reserved.

No part of this book may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, microfilming, recording, or otherwise, without written permission from the publisher.

Printed in the United States of America

BEST AVAILABLE COPY

BEST AVAILABLE COPY

ZnO-WO3




Fig. 8261—System ZnO-WO3. Mon = monoclinic; Tet = tetragonal; Cub = cubic.

A. V. Shchenev, Yu. F. Kargin, and V. M. Skorikov, Zh. Neorg. Khim., 33 [8] 2165-2167 (1988); Russ. J. Inorg. Chem. (Engl. Transl.), 33 [8] 1237-1238 (1988).

The ZnO-WO3 system was studied by X-ray diffraction, differential thermal analysis, and chemical phase analysis in the concentration range 10-85 mol% WO3. The starting materials were highly-pure (for optical glass preparation) grade tungsten(VI) oxide and highlypure grade zinc oxide. Approximately 12 specimens were prepared at 5-10 mol% intervals. Weighed specimens of the oxides were mixed, ground, and subjected to heating in stages with regrinding at each stage. (No mention was made about contamination.) The temperature was increased from 600°C to (0.9-0.95)Tfusion; the total heating time was about 120 h, and in some cases up to 200 h. X-ray diffraction confirmed that the reaction was complete. The thermal analysis was carried out on a DTA apparatus at heating and cooling rates of about 7°C min-1 using platinum crucibles and previously-heated alumina as standard. The X-ray diffraction was carried out on a diffractometer (CuKa radiation, Ni-filter). Tungsten(VI) oxide in the specimens was determined gravimetrically, and zine oxide by complexometric titration. The only compound formed in this system was normal zinc tungstate ZnWO4, with melting point 1210° ± 5°C. Zinc tungstate formed eutectics with the original components: on the tungsten(VI) oxide side at 65 mol% WO3 and 35 mol% ZnO with melting point 1122°C. The eutectic on the zinc oxide side with composition ~43 mol% WO3 and 57 mol% ZnO corresponded to a cutectic line which could be followed in the range 52-85 mol% ZnO. The more accurate determination of the composition of this cutectic and the position of the liquidus line was made difficult by the sublimation of the components at high temperatures. See Figs. 6433 and 9260 for earlier work.

S.K.S.

Al₂O₃-Nd₂O₃




Fig. 9262—System Al₂O₃-Nd₂O₃. AN - AlNdO₃: AN₂ - Al₂Nd₄O₉: A, H, and X - rare-earth oxide polymorphic forms: A and H are hexagonal; X is cubic; α -Al₂O₃ - corundum type: β -Nd-Al₂O₃ - NdAl₁₁O₁₈.

J. P. Coutures, J. Am. Ceram. Soc., 68 [3] 105-107 (1985).

The tentative phase diagram for the system Al2O3-Nd2O3 is presented. The author pointed out the discrepencies in the previous studies.1-4 The purities of Nd2O3 and Al2O3 used were 99.9% and 99.99%, respectively. Prior to use, Nd2O3 was annealed at 1200°C for 5 h in order to remove anionic impurities. The samples were prepared in air by co-melting ~30 mixtures of the starting oxides in a laboratory-scale solar furnace. Phase identification was done by room-temperature XRD (Ni-filtered CuKa radiation; goniometer scanning speed 1°C/min in 20). The liquidus and solidus lines were drawn from the results obtained by a thermal analyzer associated with a 2 kW horizontal-axis solar furnace. The temperatures were measured with an optical pyrometer under good blackbody conditions (& pyrometer, 0.65 µm; practical emmissivity, 0.99; calibration points, Al2O3 melting point 2053°C and Y2O3 melting point 2440°C). The temperature measurements expressed in the 68 IPTS are at ±10°C. The thermal analyses were performed for each composition under a 2 L/min flow of argon (~100 ppm O2) or oxygen (99.9%). The system was scanned over the 0 to 100 mol% Al2O3 composition range in 5 mol% steps except between 10 and 35 mol% Al₂O₃ and between 70 and 100

Al₂O₃-Nd₂O₃ (concl.)

mol% Al₂O₃ where 2.5 mol% steps were used. Three compounds, a β-Al₂O₃-type compound, the perovskite NdAlO₃, and Nd₄Al₂O₉, were identified. The exact composition (or composition range) of the β-Nd-Al₂O₃ phase is not discussed. The perovskite melts congruently at 2090°C; and the other compounds exhibit incongruent melting behavior: β-Nd-Al₂O₃ at 1900°C and Nd₄Al₂O₉ at 1905°C. Nd₄Al₂O₉ decomposed below 1780°C into NdAlO₃ and A-Nd₂O₃. On the Nd₂O₃-rich side, and due to high temperature transitions (A-H at ~2100°C and H-X at ~2200°C) two metatectics are observed on the liquidus line at ~2100°C, 11 mol%, and at ~2200°C, 7 mol% Al₂O₃. The author observed for a given composition a depression of liquidus and solidus temperatures due to oxygen dissolution in the melt.

- N. A. Toropov and T. P. Kiseleva, Zh. Neorg. Khim., 6 [10] 2353-2358 (1961); Russ. J. Inorg. Chem. (Engl. Transl.), 6 [10] 1193-1196 (1961).
- Transl.), 6 [10] 1193-1196 (1961).

 2. M. Mizuno, T. Yamada, and T. Noguchi, Yogyo Kyokashi, 85 [2] 90-95 (1977).
- E. Antic-Fidancev and P. Caro, C. R. Seances Acad. Sci., Ser. C, 284 [13] 471-474 (1977).
- 4. J. P. Coutures, E. Antic, and P. Caro, Mater. Res. Bull., 11 [6] 699-706 (1976).

S.K.S.

Al2O3-V2O3




Fig. 9263—System Al₂O₃-V₂O₃. Crn = corundum (Al₂O₃).

A. Muan and M. S. Najjar; "Compositions involving V2O3-Al2O3-CaO", US Patent 5,070,065, 1991.

There are strong crystallographic similarities between V2O3 and other better known sesquioxides, such as Al2O3, Fe2O3, and Cr2O3. They all have the close-packed hexagonal corundum-type structure in which cations are in octahedral coordination. Among the trivalent cations forming these sesquioxides, Al*3 stands out as being considerably different from the others (Fe*3, Cr*3, and V*3). First, Al*3 is a noble gas-type ion. Second, it is significantly smaller than the other ions and, hence, can occur fairly readily in four-fold (tetrahedral), as well as six-fold (octahedral), coordination.

There is a lack of complete solid solubility between Al₂O₃ and V₂O₃. Corundum solid solution and V₂O₃ solid solution coexist with a liquid phase along the liquidus surface of the system.

See Figs. 9221 and 9259 for a discussion of experimental methods.

M.S.N.

Al2O3-Y2O3




Fig. 9264—System Y2O3-Al2O3.

I. A. Bondar, L. N. Koroleva, and E. T. Bezruk, Izv. Akad. Nauk SSSR, Neorg. Mater., 20 [2] 257-261 (1984); Inorg. Mater. (Engl. Transl.), 20 [2] 214-218 (1984).

The starting materials were Y₂O₃ and Al₂O₃. Approximately 20 compositions were obtained by solid-phase synthesis by precipitation from nitrates and from the melt. Microscopy, X-ray diffraction, and X-ray spectral analysis were used to analyze products.

See Figs. 311, 312, 2344, and 4370 for earlier studles.

G.L.G.